

HEAD OFFICE

East Quarry
Appley Lane North
Appley Bridge
Wigan
WN6 9AE
UK

GLOBAL LOCATIONS

UK
Europe
USA
Brazil
South Africa
Antartica
Australia
& more

DISCOVER MORE

ndiver-military.com

CONTACT US

neil@ndiver.com
mel@ndiver.com
+44 (0) 1257 25 44 44

Switch Block



The Switch Block has been designed to be used with the Interspiro Divator AGA and OTS full face mask with a Medium Pressure (i.e. less than 16 bar / 232 psi) air supply. The switch block receives air hoses from the main and bailout cylinders and allows the diver to switch from the primary air supply to an alternate bailout air supply in case of low or failure of the primary supply. The switch block is attached to the diver's mask, which is in an easily accessible location so the diver can open the Switch Block valve unaided and in nil visibility conditions. It is a diver activated switched valve to change the air supply from the main cylinder (switch in horizontal position) to the bailout (turn switch 90 deg, clockwise to the vertical position).

Standards

Conforms to the requirements of EN 250:2014, respiratory equipment – open circuit self-contained compressed air diving apparatus
EN 250:2014
CE 2425
Regulation (EU) 2016/425 Personal Protective Equipment

Features

Depth rating: 0-50 metres
Breathable air: use with compressed air only, complies with EN 12021
Dimensions (LxWxD): 68.5*60*44.5mm
Weight: 230g

Materials

Housing: Brass CZ121
Finish: Chrome Plated
Spring 316 S/S
O-Rings NBR
Acetal

Temperature condition

Performance: <10°C
Storage: -30°C to +70°C
Testing: -20°C to +55°C

Flow

Main via 1st stage: >150m³/hr @ 10bar outlet / 50 bar inlet.
Bail via 1st stage: >150m³/hr @ 10bar outlet / 50 bar inlet.
Please note that hoses are not supplied with this item but can be purchased seperately



ND0000772 (Interspiro AGA)



ND0001413 (OTS)